CONCRETE STRENGTH TESTER

DATA OUTPUT

CST-D101

CST-D102



CST-D102 seperable

- Measure the strength of general building components, bridges and various concrete components (slabs, beams, columns, bridges, etc.)
- Angle, test surface, pumping, carbonization depth and other parameters can be customized according to the requirements
- The rebound body can be used for 2000 times
- USB data transmission
- The software can automatically generate the test report, and the strength curve can be customized and stored in the tester
- Storage and reading of 1000 test data
- According to JGJ/ T23-2011, the curve of rebound meter can be customized to calculate the compressive strength of concrete

software CD (included)



sander (included)

SPECIFICATION

Code	CST-D101	CST-D102
Display	OLED display	
Range	10-70N/mm²	
Accuracy	±1R	
Parameter	Mpa, N/mm², Kgf/mm²	
Impact energy	2.207J, for testing common buildings or bridge structures	
Output	USB	
Structure	one body, non-seperable	separable, the digital display unit can be reused
Memory	1000 data	
Operating temperature	-40°C~60°C	
Power supply	built-in rechargeable battery	
Dimension	280×75×60mm	
Weight	1.1Kg	

STANDARD DELIVERY

Main unit	1pc
Sander	1pc
Power adapter	1pc
USB cable and software	1pc

OPTIONAL ACCESSORY

Rebound body(CST-D102)	CST-D102-REBOUND
Digital display unit(CST-D102)	CST-D102-DISPLAY

Software (included) for uploading and storing data, printing and importing/exporting strength curves